FXLD2512B5I6
LED Light Bar

- 5 in1 Five Color LEDs (Red, Green, Blue, White, Amber)
- Adjustable White Color Temperature 3000K-7200K
- 12 - 25 Watt LEDs
- 330 Total Watts
- 5/9 Channel DMX Operation
- Flicker Free (Refresh Rate > 3000 Hz)
- Reflector Beam Angle 60°
- Control Modes: DMX, Autorun, Master/Slave and Sound Activation
- Power In/Out: Turn & Lock
- DMX Data In & Out: 3 pin XLR
- Tilt: -90° ~ +90°
- Housing: Steel
- Color: Black

The FXLD2512B5I6 is a 5 color (RGBWA) LED light bar. It is suitable for stage, disco, night club, and other artistic applications. It has several stand-alone control modes and can operate via a DMX512 external signal. Adjustable mounting brackets are included.

SPECIFICATIONS

DMX Channels:	5 / 9	IP Rating:	IP20
DMX In/Out:	3-Pin XLR	Refresh Rate:	>3.0 kHz
Power Input:	100 - 240 VAC	Size:	42.7”W x 4.9”D x 5.4”H
Power Consumption:	330 Watts	Weight:	19.8 lbs
Power Connectors:	Turn & Lock In and Out		

	5'			10'			20'		
FXLD2512B5I\60°	Beam Diameter	foot-candle	lux	Beam Diameter	foot-candle	lux	Beam Diameter	foot-candle	lux
Red	3x3	11.2	117	6x6	3.9	50	12x12	1.3	14
Green	3x3	44.9	482	6x6	16.2	174	12x12	4.4	47
Blue	3x3	69.5	639	6x6	22	226	12x12	5.6	60
White	3x3	45.3	487	6x6	16.2	175	12x12	4.4	48
Amber	3x3	13.7	142	6x6	5.9	64	12x12	1.6	18
ALL Colors	3x3	168.7	1820	6x6	60.9	657	12x12	16.3	176

To view and/or download the Owner’s Manual click here: **www.lightronics.com/manuals/fxld2512b5i6m.pdf**