

Portable Dimmers

- LED Digital Display
- 4 Channels
- 600W per Channel
- Softpatch (each dimmer)
- Dimmer Limiting
- Dimmer Curve Selection
- Architectural Interface
- AMX/Crestron Interface
- DMX-512 Protocol
- 8 Built in Chases
- Relay Mode Switchable
- Fuses
- Edison Outputs
- 120V

XC40
Portable Dimmer



The XC40 is a four circuit compact dimmer with a load capacity of 600 Watts per circuit. Each circuit is protected by a 5 Amp fuse. It can be controlled in several ways - the most common being DMX-512. Other control modes are also provided for stand alone operations. These include individual channel control and chaser functions. Individual circuits may be operated as non-dim (relay) circuits. Individual circuits may be set for one of several response curves and may be limited to less than full intensity. In addition to full soft patch capability there is a quick pack address function which enables rapid setup.

SPECIFICATIONS

Channels:	4	Fusing:	5 Amp each Channel
Channel Capacity:	600 Watts per Channel	Preheat Voltage:	Soft Start Control
Total Power:	2400 Watts	Response Curve:	Incandescent Bulbs, LED, Fluorescent, Relay Mode
Control Protocol:	DMX-512, RS-485, Architectural	Filter Rise Time:	150 Microseconds
Control Connections:	Dual 5 Pin XLR	Filter Max. Rate of Rise:	105 Milliamps / Microsecond
Power Requirements:	120VAC, 20 Amp	Full Load Voltage Drop:	3 Volts
Power Input:	Edison Plug	Efficiency:	97%
Frequency:	50 or 60Hz	Size:	8.5"L x 7"W x 2"D
		Weight:	4 Pounds

Portable Dimmers

Architect & Engineer's Specifications

The dimming system shall have 4 circuits with a load capacity of 600 Watts per circuit. Each circuit is protected by a 5 Amp fast acting fuse. An allowance of 200% overhead capacity is employed in the triac circuit design, 15 Amps per circuit, and an overhead of up to 400 Volts per circuit. The dimming system shall have a rise time of not less than 150 microseconds. A user may set dimmer attributes of Dim or Relay, unit address, and stand alone chase functions via menus. The dimming system shall use the USITT standard DMX-512 protocol, on a 5 pin XLR type connector for direct control of the dimming circuits. The microcontroller directly applies pulse width modulation to channel output drive opto-couplers without the need for any analog circuitry. The opto-couplers provide 5000 Volt isolation between the high voltage and all other circuitry.

Power requirements of the dimming system shall be a 120VAC circuit at 20 Amps. The microprocessor auto senses line frequency and will operate 50Hz or 60Hz. Load output connectors shall be Edison style connectors. Input electrical connections are made through a pigtail with connector determined when purchased. The dimming system is to be mounted using standard lighting equipment clamps. All components and sub-systems of the dimming system shall be UL recognized when specified by the user and conform to the standards set forth.

The dimming system shall be a Lightronics XC40.

To view and/or download the Owner's Manual click here: www.lightronics.com/manuals/xc40m.pdf