

# Architectural Systems

- 8 Scenes Push Button Station
- Screwless Faceplate Option
- Available in Ivory or White
- Toggle Scene Control
- Status LEDs
- Blackout
- RS-485
- Single Gang Box
- Low Voltage

## AC-1009 Remote Station



### SPECIFICATIONS

Scenes:	8 + Blackout	Power Input:	18VDC provided by AR-1202RTC
Communication Bus:	Bidirectional RS-485	Size:	2"W x 4"H x 1.5"D
Wiring:	Dual Twisted Pair Data Cable	Weight:	0.25 Pounds

### Architect & Engineer's Specifications

The AC-1009 is a wall mounted, 8 scene, digital remote for use with the Lightronics AR-1202RTC architectural dimmer. Eight LED scene indicators adjacent to their associated buttons always display the current scene, a ninth LED indicates a "blackout" status and it is adjacent to it's associated button. The AC-1009 wiring is low voltage. The AC-1009 connects to the AR-1202RTC via a shielded 4 conductor cable arranged as 2 twisted pairs. One pair connects to the data signals. The other pair carries the common and power. Scenes activated by the AC-1009 are created and stored in the AR-1202RTC. The AC-1009 can access up to 6 different scene blocks with 8 scenes in each block. No setup or turn on procedure is needed. When the AR-1202RTC dimmer is powered on, the AC-1009 will also be powered. Communication with the AC-1009 is automatically established. The unit fits into a standard single gang wall switch box.

Power Input: 18VDC provided by AR-1202RTC; Dimensions: 2"W x 4"H x 1.5"D, Weight: 0.25 Pounds.

The unit shall be the Lightronics AC-1009.

### 5 YEAR WARRANTY

The 5 year warranty is valid if the Warranty Registration card is returned to Lightronics, Inc. within 30 DAYS of the purchase date.

