

cat_rev110816

	AS-40M	AS-40D	AS-40L	SD-4102
Channels	4			
Watts/Channel	600	600	600	750
Total Wattage	2400	2400	2400	1800
Control Protocol	DMX	DMX	LMX	DMX
Built-In Chaser	8 Chases	8 Chases	8 Chases	16 Chases
Local Control	Yes	-	-	-
Dim/Non-Dim Control	Yes	Yes	Yes	-
Soft Start	Yes	Yes	Yes	-
Power Input	120VAC, 20A, 50/60 Hz	120VAC, 20A, 50/60 Hz	120VAC, 20A, 50/60 Hz	120VAC, 15A, 50/60 Hz
Input Connections	Edison			
Output Connections	One Edison/ Channel	One Edison/ Channel	One Edison/ Channel	Dual Edison/ Channel
Overload Protection	Fuses			
Filter Rise Time	150 uSec minimum			
Weight (boxed)	5 pounds	5 pounds	5 pounds	7 pounds
OPTIONS				
UB	UL-508 Compliant - 12A Mains Circuit Breaker, 1440 Watts Total Load for AS40 Series			
UT	UL-508 Compliant - Twistlock Power Input Connector for AS40 Series			
230V	230 Volt Operation for AS40 Series			