

AS62 Series	AS-62DCSL	AS-62DCSK	AS-62DC	AS-62D	AS-62L
Channels	6				
Watts/Channel	1200				
Total Wattage	7200	7200	4800	4800	4800
Control Protocol	DMX/LMX	DMX/LMX	DMX/LMX	DMX/LMX	LMX
Built-In Chaser	8 chases				
Dim/Non-Dim Control	Yes				
Soft start	Yes				
Power Input	120/240VAC 2 Hots, 30A each, 50/60 Hz	120/240VAC 2 Hots, 30A each, 50/60 Hz	Dual 120VAC, 20A each, 50/60 Hz	Dual 120VAC, 20A each, 50/60 Hz	Dual 120VAC, 20A each, 50/60 Hz
Input Connections	2' cable stub 4 Conductor, AWG#10	2' cable stub 4 Conductor, AWG#10	Dual Edison Plugs	Dual Edison Plugs	Dual Edison Plugs
Output Connections	19 Pin LINK© Socapex	19 Pin KUPO© Socapex	6 Dual Edison Sockets	6 Dual Edison Sockets	6 Dual Edison Sockets
Overload Protection	10A Circuit Breakers	10A Circuit Breakers	10A Circuit Breakers	10A Fuses	10A Fuses
Filter Rise Time	350 uSec minimum				
Weight (boxed)	12 pounds	12 pounds	10 pounds	10 pounds	10 pounds