

cat_rev130517

	AK Series	AC1109	AC2116	AF2104
Style	Button	Button	Button	Fader
Scenes	5, 3 or 2	8	16	4
Functions	5, 3 or 2 Scenes	8 Scenes and OFF	16 Scenes and OFF	4 Scenes + ON, OFF
Controls	5, 3 or 2 Scene Buttons	8 Scenes, 1 OFF	16 Scenes, 1 OFF	4 Faders + ON, OFF
Indicators	Backlit in Buttons	8 Scenes, 1 OFF	16 Scenes, 1 OFF	On, Off and Manual
Color	White	White	White	White
Addressability	6 Scene Blocks	6 Scene Blocks	6 Scene Blocks	3 Scene Blocks
Protocol	Lightronics Architectural Network (bidirectional RS-485)			
Connections	Low capacitance, shielded, two twisted pair data cable			
Wall Box Size	1 gang	1 gang	2 gang	2 gang
Weight (boxed)	1 pound			
OPTIONS				
PORT01	Portable Chassis Option for Architectural Stations with 4 pin male XLR connector			

	AF3107	AF5113	AI1001	AX0009	APP01
Style	Fader	Fader	Infrared	Interface	Switch
Scenes	6	12	13	8	2
Functions	6 Scenes and	12 Scenes and			
Controls	7 Faders + ON, OFF	13 Faders + ON, OFF	Handheld Remote	9 Inputs	Toggle Switch
Indicators	On, Off and Manual	On, Off and Manual	Remote Reception	9 Scene Outputs	-
Color	White	White	White	Black	White
Addressability	3 Scene Blocks	3 Scene Blocks	6 Scene Blocks	4 Addresses	-
Protocol	Lightronics Architectural Network (bidirectional RS-485)				Contact Closure
Connections	Low capacitance, shielded, two twisted pair data cable				3 Conductor Cable
Wall Box Size	3 gang	5 gang	1 gang	-	1 gang
Weight (boxed)	1 pound				
OPTIONS					
PORT01	Portable Chassis Option for Architectural Stations with 4 pin male XLR connector				