

# Lighting Fixtures

## Ellipsoidal

- Available in 10,19,26,36 and 50 degree beam spreads
- High Quality Optical System
- Glass Reflector
- Die Cast Aluminum Housing
- Insulated Rear handles
- Focus Control by Lens Tube Adjustment
- Interchangeable Lens Tube
- Ushio SPH 575 Halogen, 575HX605GLA or 750HX755 Lamp
- Includes Gel Holder

10 Degree: 12.25" square with 9.375" hole  
 19-50 Degree: 6.25" square with 5.375" hole

• Includes GOBO Holder  
 Size B for 2.5" and 2.75" GOBOS

- Tool Free Lamp Replacement
- Adjustable Shutters
- Tool Free centering of Lamp
- Available in White or Black
- Dimensions and Weight

10 Degree: 24"L X 21"W X 21"H, 22.0 LBS.  
 19-50 Degree: 24"L X 10.5"W X 11"H, 16.5 LBS.



### 10 Degree

Distance (ft)	80	90	100	110	120
Beam Diam.	12.8	14.4	16	17.6	19.2
FC	130	103	84	69	58

### 19 Degree

Distance (ft)	40	50	60	70	80
Beam Diam.	10.8	13.5	16.2	18.9	21.6
FC	180	115	80	59	45

### 26 Degree

Distance (ft)	30	40	50	60	70
Beam Diam.	9.9	13.2	16.5	19.8	23.1
FC	192	108	69	48	35

### 36 Degree

Distance (ft)	10	20	30	40	50
Beam Diam.	4.5	9	13.5	18	22.5
FC	815	203	90	50	32

### 50 Degree

Distance (ft)	10	20	30	40	50
Beam Diam.	5.7	11.4	13.5	22.8	28.5
FC	429	107	47	26	17

\*Calculations based on 750W HX755 Lamp