

Lighting Fixtures

- Black Fixture
- Available in 19°, 26°, 36° and 50° Beam Spreads
- 150 Total Watts
- 120W Edison LED
- LED Color Temperature: 5500K
- LED Lifespan: >50,000 Hours
- Center Beam Lux at 1 Meter Projection Distance:
 - 19°: 23500 lux , 26°: 16200 lux,
 - 36°: 12650 lux , 50°: 7500 lux
- High Quality Optical System
- Glass Reflector
- High Impact Plastic Housing
- FX Slot
- Available in White

FXLE1260W
LED Ellipsoidal LIGHTING FIXTURE



Incredibly bright and energy efficient our new LED Ellipsoidal outshines the competition. Our LED Ellipsoidal generates over 7000 lumens while consuming just 150 Watts of electricity, providing 47 lumens per Watt. Try to find a spec that beats that. The 120 Watt LED array is rated for a 100,000 hour life span, twice that of most other brands. Best of all, our affordable price leaves the others in the dark.

The FXLE1260W is a Dimmable LED ellipsoidal lighting fixture suitable for church, stage, theater, disco, night club, and other event and artistic applications. It has automatic stand alone control modes and can operate via a DMX-512 external signal.

SPECIFICATIONS			
Power Supply:	AC100V-240V, 50/60Hz	Electronic Strobe:	0-20Hz
Power Consumption:	Max. 150W	Electronic Dimmer:	0-100%
Switch Power Supply:	Built-in and Auto Switching	DMX In/Out:	3-Pin XLR
LED:	120W Edison	Display:	LED Display
LED Color Temp.:	5500K	Cooling Method:	3 Fans
LED Lifespan:	>50,000 Hours	IP Rating:	IP20
Control:	Auto, Master/Slave and DMX	Housing:	High Impact Plastic
DMX Channels:	2 Channels	Dimensions (LxWxH):	23.9" x 10.7" x 11.1"
		Weight:	12 pounds

	10'			20'			30'		
	Beam Dia. (WxH)	foot candle	lux	Beam Dia. (WxH)	foot candle	lux	Beam Dia. (WxH)	foot candle	lux
FXLE1260W19	-	-	-	7x7	230	2500	11x11	111	1214
FXLE1260W26	-	-	-	10x10	160	1723	16x16	58.5	628
FXLE1260W36	-	-	-	14x14	111.5	1200	20x20	48	516
FXLE1260W50	10x10	200	2160	16x16	50	635	-	-	-

To view and/or download the Owner's Manual click here: www.lightronics.com/manuals/fxle1260wm.pdf